



Supplies Needed

#40000653 Gold Metal Macrame Ring, 6" (1)

#34733002 Wood Bead Mix, 150G (1 pk)

Bulky Yarn of Choice (approx. 26 yds or more for longer hanging)

Tools Needed

Scissors

Craft Glue

Ruler or Yardstick

Scotch Tape

*#24200 Bead Reamer (*optional but can be helpful)

Techniques to Know (see images)

Lark's Head Knot

Double Half Hitch Knot

Reverse Double Half Hitch Knot

(You will need a pegboard or perpendicular surface along with hooks, nails, or pegs to hang the macrame ring and working cords onto while making the wall hanging.)

INSTRUCTIONS:

1. You can choose to leave the gold metal macrame ring uncovered. Another option is to cover it w/ yarn. To do that, cut a 4' length of yarn. Wrap the yarn around the entire circumference of the macrame ring. When the yarn ends meet, tie the two ends together into a secure knot. Cut the tails of the knot and place a dab of glue on the knot to secure it. Allow to dry.
2. Hang the ring up on a hook, nail, or peg while working on your wall hanging.
3. Cut eleven 6 ½ foot lengths of yarn. Use a lark's head knot to attach the middle of each length of yarn along the top of the macrame ring. From here forward, I will refer to the yarn as **cord**. You now have 22 working cords.
4. Below the macrame ring, place hooks, nails, or pegs on the left and right side of the macrame ring. Starting with the middle two working cords, cross the right cord over the left cord. Bring those cords behind the bottom of the ring and drape them over the hooks, nails, or pegs you placed on the left and right side below the macrame ring.

5. Continue crossing the next cord on the center right over the next cord on the center left of the macrame ring, bring them behind the macrame ring, and drape them. Continue this process until all cords have been crossed and draped, in order.
6. Beginning with the first cords draped onto the hook on each side of the macrame ring, use a double half hitch knot to attach the cord on the left to the bottom left of the macrame ring and use a reverse double half hitch knot to attach the cord on the right to bottom right side of the macrame ring.
7. Continue attaching all the cords onto the bottom left and right sides of the ring, in the order they were crossed, until all cords are attached to the bottom of the ring. There is now a crisscross design in the middle of the macrame ring.
8. Choose the cords you wish to slide large dark brown wooden beads onto. (We used 13 beads. A bead reamer can be used to ream out any uneven edges inside the holes of the wooden beads.) Wrap a 2" length of scotch tape around the bottom of those cords. Use your fingers to work those lengths of tape into a point that will fit through the holes in the wooden beads.
9. Bring the points of tape through the holes in the wooden beads and slide the beads onto the cords. Position the beads on the cords as desired.
10. Trim the bottom of the cords as desired.

SKILL LEVEL: Advanced Beginner

APPROXIMATE TIME: 1-2 Hrs.